

EZSIGNAGE SIGNAGE MEDIA PLAYER



Specification

Model	TX3
Brand	EZSignage
Processor	Amlogic S905X3 ARM Quad Core Cortex-A55
GPU	ARM Mali G31 MP2
RAM	4 GB DDR3
Flash	32GB eMMC
Bluetooth	Bluetooth 4.1
WiFi	802.11b/g/n/ac 2.4G/5.8G* 2 WiFi
I/O	RJ45: 1 DC-In: 1 USB2.0: 1 USB3.0: 1 HDMI2.0a: 1 IR Receiver: 1 Coaxial Digital Audio: 1 Micro SD Card Reader: 1
OS	Android 9.0
UI	ALICE
Accessory	HDMI Cable: 1 User Manual: 1 5V/2A Adapter: 1 Gift Box Packing: 1 IR Remote Control: 1
Remote	Yes
Product	105*105*15mm Plastic
Gift Box	0.5KG 155*137*80mm



4K
@60fps



Android
9.0



1080P Oline
Video Chat



HEVC

DETAILED SPECIFICATION

OS	Android 9.0
CPU	Amlogic S905X3 64-bit Quad Core, ARM® Cortex™ A55
Picture	4Kx2K@60fps
GPU	ARM G31 MP2
RAM	4GB DDR3
ROM	32GB eMMC
Wifi	IEEE 802.11 a/b/g/n/ac, 2.4GHz / 5GHz
Bluetooth	4.1
Ethernet	10/100/1000Mbps
LED Indicator	Support
Video/Picture Decoder	- Profile-2 up to 4Kx2K@60fps
	- H.265 MP-10@L5.1 up to 4Kx2K@60fps
	- AVS2-P2 Profile up to 4Kx2K@60fps
	- H.264 AVC HP@L5.1 up to 4Kx2K@30fps
	- MPEG-4 ASP@L5, WMV/VC-1, AVS-R16/AVS-R2 JiZhun Profile, MPEG-2, MPEG-1, and RealVideo 8/9/10 up to 1080p60
	- Multiple language and multiple format sub-title video support
	- MJPEG and JPEG unlimited pixel resolution (ISO/IEC-10918)
	- Support JPEG thumbnail, scaling, rotation and transition effects
- Supports mkv, wmv, mpg, mpeg, dat, avi, mov, iso, mp4, rm, and jpg file formats	
Video/Picture Encoder	*Independent JPEG and H.264 with configurable performance/bitrate
	*JPEG image
	*H.265/H.264 video encoding up to 1080p60 with low latency
Port	1*RJ45
	1*DC-in
	1*USB 2.0, 1*USB 3.0
	1*HDMI
	1*Coaxial Digital Audio
	1*Micro SD Card Reader
Accessories	1. HDMI cable *1
	2. IR Remote *1
	3. User Manual *1
	4. Package box *1
	5. Power adapter *1

